

MATERIAL SAFETY DATA SHEET

LEX INTERNATIONAL, INC.
PO BOX 10280
PHOENIX, AZ 85064-0280

Date: SEPT. 26, 2002
MSDS No: ATI /08
Revision: NONE

| | |
|---------------------|---------------------|
| HEALTH HAZARD | 1 – Slight |
| FLAMMABILITY HAZARD | 1 – Slight |
| REACTIVITY HAZARD | 0 – Minimal |
| PERSONAL PROTECTION | B – Glasses, Gloves |

SECTION I. MATERIAL IDENTIFICATION

Trade / Material Name: LEX ADVANCED PAINT SEALANT
Description: AUTOMOTIVE POLISH & SEALANT
Chemical Name: POLYMER EMULSION
Manufacturer: ATI
Telephone: (888) 488-9343
Fax: (602) 285-4690

SECTION II. HAZARDOUS INGREDIENTS

| | | | |
|------------------|---------------------|-------|-----------|
| Ingredient Name: | DEODORIZED KEROSENE | PEL: | 500 PPM |
| CAS Number | 8008-20-6 | TLV: | 100 PPM |
| Percentage | 7.20 | IDLH: | 10000 PPM |

SECTION III. PHYSICAL DATA

Appearance & Odor: PALE YELLOW, MILK-LIKE LIQUID / PASTILLE SCENT.

| | | | |
|-------------------------------|------|--|-----------|
| Boiling point (degrees F.): | 217 | Specific gravity (H ₂ O = 1): | 1.01 |
| Water solubility (%): | 81.6 | V.O.C. (grams/liter): | 419 |
| Vapor density (air = 1): | 2.1 | Melting point (degrees F.): | 20 |
| Vapor pressure @ 20C. (mm Hg) | 16.3 | pH range: | 8.0 – 8.4 |

SECTION IV. FIRE AND EXPLOSION DATA

Flash Point and Method: N/A
Autoignition Temperature: N/A
Flammable Limits in Air: LEL: 13% / UEL: 23%
Extinguishing media: WATER FOG; DRY CHEMICAL; CO₂; FOAM.
Special Fire Fighting Procedures: PROTECTIVE CLOTHING; RESPIRATOR.
Unusual Fire and Explosion Hazards: DO NOT SPRAY NEAR OPEN FLAME, HOT ENGINES OR DEVICES THAT MAY SPARK.

Note: Although LEX Paint Sealant is a non-flammable liquid, lingering vapors given off by the product's spray may support combustion. Adequate ventilation is essential when using this product around potential sources of ignition.

MATERIAL SAFETY DATA SHEET

LEX INTERNATIONAL, INC.
PO BOX 10280
PHOENIX, AZ 85064-0280

Date: SEPT. 26, 2002
MSDS No: ATI /08
Revision: NONE

SECTION V. REACTIVITY DATA

MATERIAL IS STABLE. HAZARDOUS POLYMERIZATION CANNOT OCCUR

| | |
|-----------------------------------|-----------------------------------|
| Chemical incompatibilities: | STRONG OXIDIZING AGENTS |
| Conditions to avoid: | NONE |
| Hazardous decomposition products: | CO ₂ ; SO ₂ |

SECTION VI. HEALTH HAZARD INFORMATION

THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY OSHA, NTP, IARC

| | |
|---|--|
| Summary of risks: | CONTACT MAY CAUSE EYE IRRITATION. PROLONGED CONTACT WITH SKIN CAN CAUSE IRRITATION. EXCESSIVE INHALATION CAN CAUSE DIZZINESS AND HEADACHE. |
| Medical conditions that may be aggravated by contact: | PREEXISTING DISORDERS OF THE LIVER OR KIDNEYS, EYES, SKIN, OR RESPIRATORY SYSTEM MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. |
| Target organs: | LIVER, KIDNEYS. |
| Primary entry route(s): | EYE CONTACT; SKIN CONTACT; BREATHING PASSAGES. |
| Acute effect(s): | EYE/SKIN IRRITATION; DIZZINESS; HEADACHE AND NAUSEA FROM EXCESSIVE INHALATION. |
| Chronic effect(s): | ASPIRATION OF PRODUCT INTO LUNGS (DUE TO VOMITING) CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. |

Signs & symptoms of overexposure:

| | |
|--------------|-------------------------------------|
| Eye contact | - REDNESS; TEARING; BLURRED VISION. |
| Skin contact | - REDNESS; BLISTERING. |
| Inhalation | - DIZZINESS; HEADACHE. |
| Ingestion | - NAUSEA; CRAMPS; DIARRHEA. |

First Aid:

| | |
|--------------|---|
| Eye contact | - FLUSH WITH WATER FOR 10 MINUTES; GET MEDICAL ATTENTION. |
| Skin contact | - WASH WITH SOAP & COOL WATER. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. |
| Inhalation | - MOVE TO FRESH AIR. |
| Ingestion | - DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY FOR INSTRUCTIONS. |

MATERIAL SAFETY DATA SHEET

LEX INTERNATIONAL, INC.
PO BOX 10280
PHOENIX, AZ 85064-0280

Date: SEPT. 26, 2002
MSDS No: ATI /08
Revision: NONE

SECTION VII. LEAK AND DISPOSAL PROCEDURES

Spill and/or leak procedures: CONTAIN AND COLLECT WITH ABSORBENT MATERIAL.
Large spills: VENTILATE AREA. CONTAIN SPILL WITH INERT ABSORBENT, OR, MOP UP.
Waste management/disposal: IN ACCORDANCE WITH STATE AND FEDERAL REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

Personal protective equipment:

Goggles - SAFETY GLASSES; EYE WASH STATION AVAILABLE.
Gloves - RUBBER GLOVES.
Respirator - RESPIRATOR MASK IN CONFINED AREAS OR EMERGENCY SITUATIONS.

Workplace considerations:

Ventilation - PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Safety stations:

Eye contact - EYE WASH STATIONS.
Contaminated equipment/clothing - LAUNDRY BEFORE REUSING.

SECTION IX. SPECIAL PRECAUTIONS

Storage segregation: KEEP AWAY FROM SOURCES CAPABLE OF IGNITING PRODUCT CONTAINER / CARTON.
Special handling/storage: NONE.
Other precautions: NONE.
DOT class: CLEANING COMPOUND.
NOI: CLASS 55.
Prepared/revised by: STEVEN D. LEIS
Date: SEPTEMBER 26, 2002

THIS PRODUCT MATERIAL SAFETY DATA SHEET PROVIDES HEALTH AND SAFETY INFORMATION. THE PRODUCT IS TO BE USED IN APPLICATIONS CONSISTENT WITH COMPANY LITERATURE AND PRODUCT DIRECTIONS. INDIVIDUALS HANDLING THIS PRODUCT SHOULD HAVE ACCESS TO THIS INFORMATION. FOR ANY OTHER USES, EXPOSURES SHOULD BE EVALUATED SO THAT APPROPRIATE HANDLING PRACTICES AND TRAINING PROGRAMS CAN BE ESTABLISHED TO ENSURE SAFE WORKPLACE OPERATIONS. PLEASE CONTACT LEX INTERNATIONAL, INC. FOR FURTHER INFORMATION, IF NECESSARY.